

References

- Albright, J. N., and Pearson, C. F., 1980, Location of Hydraulic Fractures Using Microseismic Techniques: Society of Petroleum Engineers, 55th Annual and Technical Conference and Exhibition, Dallas, Texas, paper SPE 9509, September 21-24.
- Allen, R., 1978, Automatic earthquake recognition and timing from single traces.: Bulletin of the Seismological Society of America, **68**, 1521–1532.
- Anant, K. S., and Dowla, F. U., 1997, Wavelet transform methods for phase identification in three-component seismograms: Bulletin of the Seismological Society of America, **87**, no. 6, 1598–1612.
- Baer, M., and Kradolfer, U., 1987, An automatic phase picker for local and teleseismic events: Bulletin of the Seismological Society of America, **77**, no. 4, 1437–1445.
- Bai, C.-Y., and Kennett, B. L. N., 2000, Automatic phase-detection and identification by full use of a single three-component broadband seismogram: Bulletin of the Seismological Society of America, **90**, no. 1, 187–198.
- Baisch, S., Bohnhoff, M., Ceranna, L., Tu, Y., and Harjes, H.-P., 2002, Probing the crust to 9 km depth: Fluid injection experiments and induced seismicity at the KTB superdeep drilling hole, Germany: Bulletin of the Seismological Society of America, **92**, 2369–2380.
- Baker, T., Granat, R., and Clayton, R. W., 2005, Real-time earthquake location using Kirchhoff reconstruction: Bulletin of the Seismological Society of America, **95**, no. 2, 699–707.
- Bakun, W. H., and McEvilly, T. V., 1984, Recurrence models and Parkfield, California, earthquakes: Journal of Geophysical Research, **89**, 3051–3058.
- Bakun, W. H., Aagaard, B., Dost, B., Ellsworth, W. L., Hardbeck, J. L., Harris, R. A., Ji, C., Johnston, M. J. S., Langbein, J., Lienkaemper, J. J., Michael, A. J., Nadeau, R. M., Reasenburg, P. A., Reichle, M. S., Roeloffs, E. A., Shakai,

REFERENCES

- A., Simpson, R. W., and Waldhauser, F., 2005, Implications for prediction and hazard assessment from the 2004 Parkfield earthquake: *Nature*, **437**, 969–974.
- Bataille, K., and Chiu, J. M., 1991, Polarization analysis of high-frequency, three-component seismic data: *Bulletin of the Seismological Society of America*, **81**, no. 2, 622–642.
- Bland, H., and Stewart, R. R., 1996, Geophone orientation, location, and polarity checking for 3-c seismic surveys: *CREWES Research Report*, **8**, no. chapter 3.
- Bolt, B. A., 1960, The revision of earthquake epicentres, focal depths and origin times using a high-speed computer: *Geophys. J. Roy. Astr. Soc.*, **3**, 433–440.
- Boness, N., and Zoback, M., 2006, A multiscale study of the mechanisms controlling shear velocity anisotropy in the San Andreas Fault Observatory at Depth: *Geophysics*, **71**, no. 5.
- Buske, S., Gutjahr, S., Rentsch, S., and Shapiro, S., 2006, Active and passive seismic imaging of the San-Andreas-Fault-System: 12th International Symposium on deep seismic profiling of the continents and their margins, 25-29 September, Hayama, Japan, SDE-P16.
- Carminati, E., Negredo, A., Valera, J., and Doglioni, C., Subduction-related intermediate-depth and deep seismicity in Italy: insights from thermal and rheological modelling: *Physics of the Earth and Planetary Interiors*, **149**, 65–79.
- Červený, V., 2001, *Seismic Ray Theory*: Cambridge University Press, 713 pages.
- Chapman, C. H., 2004, *Fundamentals of Seismic Wave Propagation*: Cambridge University Press.
- Chavarría, J., Malin, P., and Shalev, E., 2004, The SAFOD Pilot Hole seismic array: Wave propagation effects as a function of sensor depth and source location: *Geophysical Research Letters*, **31**, no. L12S07, doi:10.1029/2003GL019382.
- Cichowicz, A., 1993, An automatic S-phase picker: *Bulletin of the Seismological Society of America*, **83**, no. 1, 180–189.
- Costain, J., and Bollinger, G., 1991, Correlations between streamflow and intraplate seismicity in the central Virginia, U.S.A., seismic zone: evidence for possible climatic controls: *Tectonophysics*, **186**.
- Curtis, C., Kopper, R., Decoster, E., Guzmán-García, A., Huggins, C., Knauer, L., Minner, M., Kupsch, N., Linares, L., Rough, H., and Waite, M., 2002, Heavy oil reservoirs: *Oilfield Review*, **14**, 30–51.
- De Meersman, K., van der Baan, M., and Kendall, J.-M., 2006, Signal extraction and automated polarization analysis of multicomponent array data: *Bulletin of the Seismological Society of America*, **96**, no. 6, 2415–2430.

- Doser, D. I., Baker, M. R., and Mason, D. B., 1991, Seismicity in the War-Wink gas field, Delaware Basin, west Texas, and its relationship to petroleum production: *Bulletin of the Seismological Society of America*, **81**, no. 3, 971–986.
- Drijkoningen, G. G., Rademakers, F., Slob, E. C., and Fokkema, J. T., 2006, A new elastic model for ground coupling of geophones with spikes: *Geophysics*, **71**, no. 2, Q9–Q17.
- Dyman, T., and Condon, S., 2006, Assessment of undiscovered conventional oil and gas resources - Upper Jurassic - Lower Cretaceous Cotton Valley Group, Jurassic Smackover Interior Salt Basins Total Petroleum System, in the East Texas Basin and Louisiana-Mississippi Salt Basins Provinces: U.S. Geological Survey Digital Data Series DDS-69-E, Chapter 2, 48 p.
- Earle, P. S., and Shearer, P. M., 1994, Characterization of global seismograms using an automatic-picking algorithm: *Bulletin of the Seismological Society of America*, **84**, no. 2, 366 – 376.
- Feigner, B., and Grasso, J.-R., 1990, Seismicity Induced by Gas Production I: Correlation of Focal Mechanisms & Dome Structure: *Pure and Applied Geophysics*, **134**, 405–426.
- Flinn, E. A., 1960, Local earthquake location with an electronic computer: *Bulletin of the Seismological Society of America*, **50**, 467–470.
- Flinn, E., 1965, Signal analysis using rectilinearity and direction of particle motion: *IEEE proc*, **53**, 1874–1876.
- Franco, R. D., and Musacchio, G., 2001, Polarization filter with singular value decomposition: *Geophysics*, **66**, no. 3, 932–938.
- Fuchs, K., and Müller, G., 1971, Computation of synthetic seismograms with the reflectivity method and comparison with observations.: *Geophys. J. Roy.Astr.Soc*, **23(4)**, 417–433.
- Gajewski, D., and Tessmer, E., 2005, Reverse modelling for seismic event characterization: *Geophysical Journal International*, **163**, no. 1, 276–284.
- Geiger, L., 1910, Herdbestimmung bei Erdbeben aus den Ankunftszeiten: *Nachrichten von der Königlichen Gesellschaft der Wissenschaften zu Göttingen, Mathematisch-Physikalische Klasse*, pages 331–349.
- Grasso, J.-R., and Feigner, B., 1990, Seismicity induced by gas production ii: lithology correlated events, induced stresses & deformation: *Pure and Applied Geophysics*, **134**, 427–450.
- Green II, H. W., 2003, Tiny triggers deep down: *Nature*, **424**, 893–894.
- Greenhalgh, S. A., and Mason, I. M., 1995, Orientation of a downhole triaxial geophone: *Geophysics*, **60**, no. 4, 1234–1237.

REFERENCES

- Hainzl, S., Kraft, T., Wassermann, J., Igel, H., and Schmedes, E., 2006, Evidence for rainfall-triggered earthquake activity: *Geophysical Research Letters*, **33**, no. L19303, doi:10.1029/2006GL027642.
- Harris, R. A., and Arrowsmith, J. R., 2006, Introduction to the special issue on the 2004 Parkfield Earthquake and the Parkfield Earthquake Prediction Experiment: *Bulletin of the Seismological Society of America*, **96**, no. 4B, S1–10.
- Hearn, S., and Hendrick, N., 1999, A review of single-station timedomain polarisation analysis techniques: *J. Seis. Expl.*, **8**, 181–202.
- Hendrick, N., and Hearn, S., 1999, Polarisation analysis: What is it? Why do you need it? How do you do it?: *Exploration Geophysics*, **30**, 177–190.
- Hickman, S., Zoback, M., and Ellsworth, W., 2004, Introduction to special section: Preparing for the San Andreas Fault Observatory at Depth: *Geophysical Research Letters*, **31**, no. L12S01, doi:10.1029/2004GRL020688.
- House, L., 1987, Locating microearthquakes induced by hydraulic fracturing in crystalline rock: *Geophysical Research Letters*, **14**, no. 9, 919–921.
- Ishimaru, A., 1978, *Wave Propagation and Scattering in Random Media*, volume 2: Academic Press, New York, 572 pages.
- Jackson, L. B., 1989, *Digital Filters and Signal Processing*: Kluwer Academic Publishers, second edition.
- Joswig, M., 1999, Automated Processing of seismograms by SparseNet: *Seismological Research Letters*, **70**, 705–711.
- Jurkevics, A., 1988, Polarization analysis of three-component array data: *Bulletin of the Seismological Society of America*, **78**, no. 5, 1725–1743.
- Kravtsov, Y. A., and Orlov, Y. I., 1990, *Geometrical optics of inhomogeneous media*: Springer Verlag, Berlin, Heidelberg.
- Lay, T., and Wallace, T. C., 1995, *Modern global seismology*: Academic Press, 521 pages.
- Lee, W. H. K., and Lahr, J. C., 1975, HYPO71 (revised): A computer program for determining hypocenter, magnitude, and first motion pattern of local earthquakes: U.S. Geological Survey Open-File Report 75-311.
- Li, X., and Crampin, S., 1991, Complex component analysis of shear wave splitting: theory: *Geophysical Journal International*, **107**, 597–604.
- Lomax, A., Virieux, J., Volant, P., and Berge, C., 2000, Probabilistic earthquake location in 3D and layered models: Introduction of a Metropolis-Gibbs method and comparison with linear locations.: In *Advances in Seismic Event Location*. Thurber and Rabinowitz (eds.), Kluwer Academic Publishers, pages 101–134.

- Maxwell, S., and Urbancic, T., 2001, The role of passive microseismic monitoring in the instrumented oil field: *The Leading Edge*, **20**, no. 6, 636–639.
- McMechan, G. A., Luetgert, J. H., and Mooney, W. D., 1985, Imaging of earthquake sources in Long Valley Caldera, California, 1983: *Bulletin of the Seismological Society of America*, **75**, no. 4, 1005–1020.
- McMechan, G. A., 1982, Determination of source parameters by wave field extrapolation: *Geophysical Journal of the Royal Astronomical Society*, **71**, 613–628.
- Meehan, D. N., and Verma, S. K., 1994, Improved reservoir characterization in low-permeability reservoirs with geostatistical models: paper SPE 28608 presented at the 69th Annual Technical Conference and Exhibition of the Society of Petroleum Engineers held in New Orleans, LA. USA, 25-28 September 1994.
- Meltzner, A. J., and Wald, D. J., 1999, Foreshocks and aftershocks of the great 1857 California earthquake: *Bulletin of the Seismological Society of America*, **89**, no. 4, 1109–1120.
- Nadeau, R., Antolik, M., Johnson, P. A., Foxall, W., and McEvelly, T. V., 1994, Seismological studies at Parkfield III: Microearthquake clusters in the study of fault-zone dynamics: *Bulletin of the Seismological Society of America*, **84**, 247–263.
- Oppenheim, A. V., and Schaffer, R. W., 1989, *Discrete-Time Signal Processing*: Prentice-Hall, Englewood Cliffs, NJ.
- Park, J., Vernon, F. L. I., and Lindberg, C. R., 1987, Frequency dependent polarization analysis of high-frequency seismograms: *J. Geophys. Res.*, **92**, 12664–12674.
- Peebles, F. W. L., and Corey, A. H., 1912, Probability method for the determination of earthquake epicenters from the arrival time only: *Bulletin St. Louis University*, **8**, 60–71.
- Press, W. H., Flannery, B. P., Teukolsky, S. A., and Vetterling, W. T., 1992, Runge-Kutta Method and Adaptive Step Size Control for Runge-Kutta. 16.1 and 16.2 in *Numerical Recipes in FORTRAN: The Art of Scientific Computing*: Cambridge University Press, 2nd edition.
- Pujol, J., 1992, Joint hypocentral location in media with lateral velocity variations and interpretation of the station corrections: *Physics of the Earth and Planetary Interiors*, **75**, no. 1-3, 7–24.
- Pullan, S. E., 1990, Recommended standard for seismic (radar) files in the personal computer environment: *Geophysics*, **55**, no. 09, 1260–1271.

REFERENCES

- Rabiner, L. R., and Schafer, R. W., 1978, *Digital Processing of Speech Signals*: Prentice-Hall, Englewood Cliffs, NJ.
- Rabinowitz, N., 1988, Microearthquake location by means of nonlinear simplex procedure: *Bulletin of the Seismological Society of America*, **78**, no. 1, 380–384.
- Roecker, S., Thurber, C., and McPhee, D., 2004, Joint inversion of gravity and arrival time data from Parkfield: New constraints on structure and hypocenter locations near the SAFOD drill site: *Geophysical Research Letters*, **31**, no. L12S04, doi:10.1029/2003GL019396.
- Royer, J.-J., and Voillemont, J.-C., 2005, Estimating heterogeneous reservoir permeability from induced microseismicity: *SEG Technical Program Expanded Abstracts*, **24**, no. 1, 1393–1396.
- Rutledge, J. T., and Phillips, W. S., 2002, A comparison of microseismicity induced by gel-proppant- and water-injected hydraulic fractures, Carthage Cotton Valley gas field, East Texas.: 72nd Annual International Meeting, SEG, Expanded Abstracts, pages 2393–2396.
- Rutledge, J. T., and Phillips, W. S., 2003, Hydraulic stimulation of natural fractures as revealed by induced microearthquakes, Carthage Cotton Valley gas field, East Texas: *Geophysics*, **68**, no. 2, 441–452.
- Rutledge, J. T., Albright, J. N., Fairbanks, T. D., Murphy, M. B., and Roberts, P. M., 1990, Microseismic monitoring of the Chaveroo oil field, New Mexico: *SEG Technical Program Expanded Abstracts*, **9**, no. 1, 237–240.
- Rutledge, J. T., Phillips, W. S., House, L., and Zinno, R., 1998, Microseismic mapping of a Cotton Valley hydraulic fracture using decimated downhole arrays: 68th Annual International Meeting, SEG, Expanded Abstracts, pages 338–341.
- Rutledge, J. T., Phillips, W. S., and Mayerhofer, M. J., 2004, Faulting induced by forced fluid injection and fluid flow forced by faulting: An interpretation of hydraulic-fracture microseismicity, Carthage Cotton Valley gas field, Texas: *Bulletin of the Seismological Society of America*, **94**, 1817–1830.
- Sambridge, M. S., and Kennett, B., 1986, A novel method of hypocentre location: *Geophysical Journal of the Royal Astronomical Society*, **87**, 679–697.
- Sambridge, M. S., and Kennett, B. L. N., 2001, Seismic Event Location: Nonlinear Inversion Using a Neighbourhood Algorithm: *Pure and Applied Geophysics*, **158**, 241–257.
- Saragiotis, C. D., Hadjileontiadis, L. J., and Panas, S. M., 2002, PAI-S/K: A Robust Automatic Seismic P Phase Arrival Identification Scheme: *IEEE Transactions on Geoscience and Remote Sensing*, **40**, no. 6, 1395 – 1404.

- Scholz, C., 2002, *The Mechanics of Earthquakes and Faulting*: Cambridge University Press.
- Segall, P., 1989, Earthquakes triggered by fluid extraction: *Geology*, **17**, no. 10, 942–946.
- Shapiro, S. A., Huenges, E., and Borm, G., 1997, Estimating the crust permeability from fluid-injection-induced seismic emission at the KTB site: *Geophysical Journal International*, **131**, no. 2.
- Shapiro, S. A., Audigane, P., and Royer, J.-J., 1999, Large-scale in situ permeability tensor of rocks from induced microseismicity: *Geophysical Journal International*, **137**, no. 1, 207–213.
- Shapiro, S. A., Rentsch, S., and Rothert, E., 2005, Characterization of hydraulic properties of rocks using probability of fluid-induced microearthquakes: *Geophysics*, **70**, no. 2, F27–F33.
- Shapiro, S. A., Dinske, C., and Rothert, E., 2006, Hydraulic-fracturing controlled dynamics of microseismic clouds: *Geophysical Research Letters*, **33**, no. L14312, doi:10.1029/2006GL026365.
- Shapiro, S. A., 2000, An inversion for fluid transport properties of three-dimensionally heterogeneous rocks using induced microseismicity: *Geophysical Journal International*, **143**, no. 30, 931–936.
- Sheriff, R. E., 2002, *Encyclopedic dictionary of applied geophysics*: Society of Exploration Geophysicists, 429 pages, 4th edition.
- Sieh, K. E., 1978a, Central California foreshocks of the great 1857 earthquake: *Bulletin of the Seismological Society of America*, **68**, no. 6, 1731–1749.
- Sieh, K. E., 1978b, Slip along the San Andreas fault associated with the great 1857 earthquake: *Bulletin of the Seismological Society of America*, **68**, no. 5, 1421–1448.
- Strelitz, R. A., 1978, Moment tensor inversions and source models: *Geophys. J. R. Astr. Soc.*, **52**, 359–364.
- Talwani, P., and Acree, S., 1985, Pore pressure diffusion and the mechanism of reservoir-induced seismicity: *Pure and applied geophysics*, pages 947–965.
- Tatham, R. H., and McCormack, M. D., 1991, *Multicomponent seismology in petroleum exploration*: Society of Exploration Geophysicists, 248 pages.
- Thurber, H. C., and Rabinowitz, N., 2000, *Advances in seismic event location*: Kluwer Academic Publishers, 267 pages.

REFERENCES

- Thurber, C., Roecker, S., Zhang, H., Baher, S., and Ellsworth, W., 2004, Fine-scale structure of the San Andreas fault zone and location of the SAFOD target earthquakes: *Geophysical Research Letters*, **31**, no. L12S02, doi:10.1029/2003GL019398.
- Urbancic, T. I., Shumila, V., Rutledge, J. T., and Zinno, R. J., 1999, Determining hydraulic fracture behavior using microseismicity: Vail Rocks '99, 37th US Rock Mechanics Symposium, Vail, Colorado, pages 991–996.
- Urbancic, T. I., 1998, Cotton valley hydraulic fracture imaging project: Phase II (CGU21-9) fracture imaging using microseismic event locations: Engineering Seismology Group Canada Report ESG98-11, Report to Gas Research Institute.
- Vidale, J. E., 1986, Complex polarization analysis of particle motion: *Bulletin of the Seismological Society of America*, **76**, no. 5, 1393–1405.
- Walker Jr., R. N., 1997, Cotton valley hydraulic fracture imaging project: Society of Petroleum Engineers (SPE) Annual Technical Conference and Exhibition, paper 38577.
- Warpinski, N. R., 1994, Interpretation of hydraulic fracture mapping experiments: Society of Petroleum Engineers (SPE) Annual Technical Conference and Exhibition, paper 27985.
- Wescott, W. A., 1983, Diagenesis of the Cotton Valley Sandstone (Upper Jurassic), East Texas: Implications for tight gas formation pay recognition: *American Association of Petroleum Geologists Bulletin*, **67**, 1002–1013.
- Yerkes, R., and Castle, R., 1976, Seismicity and faulting attributable to fluid extraction: *Engineering Geology*, **10**, 151–167.
- Zeng, X., and McMechan, G. A., 2006, Two methods for determining geophone orientations from VSP data: *Geophysics*, **71**, no. 4, V87–V97.
- Zhang, H., Thurber, C., and Rowe, C., 2003, Automatic p-wave arrival detection and picking with multiscale wavelet analysis for single-component recordings: *Bulletin of the Seismological Society of America*, **93**, no. 5, 1904 – 1912.
- Zoback, M., and Harjes, H., 1997, Injection-induced earthquakes and crustal stress at 9 km depth at the KTB deep drilling site, Germany: *Journal of Geophysical Research*, **102**, no. 18.
- Zoback, M., Hickman, S., and Ellsworth, W., 2007, Earthquake studies: The role of fault zone drilling: *Treatise on Geophysics*, in press.
- Zoback, M. D., 1991, State of stress and crustal deformation along weak transform faults: *Royal Society of London Philosophical Transactions Series A*, **337**, 141–150.

List of Figures

1.1 Sketch of two industrial applications where reservoir stimulation induces seismicity.	2
2.1 Distribution of global seismicity from 2005 to 2007.	8
2.2 Failure criteria related to the stress state of the rock.	9
2.3 Schematic representation of the interaction of frame work stresses and pore pressure	10
2.4 The components of the moment tensor represent nine different force couples.	12
2.5 Radiation pattern of a double couple in the x-z-plane separated into its components for the P-wave (blue), SH-wave(red) and SV-wave (green), respectively.	15
2.6 Geometry of propagation direction and polarization directions for P-waves (a), S-waves (b), Rayleigh waves (c) and Love waves (d).	16
2.7 Polarization parameter sketch.	18
2.8 Aquisition geometry for synthetic data radiated from a double couple source in the center of the model. The radiation pattern of the S-waves is color-coded: green for SV-waves and red for SH-waves.	20
2.9 Polarization analysis of synthetic data generated using a double couple source and calculated polarization parameters.	22
2.10 Polarization analysis of synthetic data generated using two double couple sources in a homogeneous isotropic medium.	24

List of Figures

2.11	The ray path must be in the direction of the slowness vector and orthogonal to the wavefronts.	28
3.1	Scheme of a detection algorithm that combines STA/LTA ratios, spectrogram analysis and polarization analysis.	32
3.2	Flowchart of the method.	34
3.3	Scheme of energy back-propagation.	35
3.4	Scheme of an image obtained by initial-value ray tracing, energy weighting and summation over three receivers.	37
3.5	Acquisition geometry of the first synthetic data example.	40
3.6	Synthetic data radiated from an explosion source and recorded at arbitrarily placed three-component surface receivers.	40
3.7	Image of the source using 20 arbitrarily placed surface stations.	41
3.8	Acquisition geometry of the second synthetic data example simulating a monitoring well.	42
3.9	Synthetic data radiated from an explosion source and recorded at a vertical array of 20 three-component receivers.	42
3.10	Image of the source using 20 receivers in a vertical monitoring well.	43
3.11	Acquisition geometry of the third synthetic data example.	44
3.12	Synthetic data set generated with a double couple source in the x-z plane.	44
3.13	Scheme of phase detection and identification using array-specific polarization features.	46
3.14	Source image obtained with the location method that uses averaged polarization information.	46
3.15	Location errors with increasing mean noise level.	47
3.16	Illustration of estimating the receiver orientation.	49
3.17	Consequences of a disturbed receiver fidelity.	50
3.18	Errors of observed emergence angles due to receiver fidelity disturbance.	51
3.19	3C synthetic data of receivers with disturbed component fidelity.	53

3.20	Estimation error of receiver fidelity for different number of analyzed noise samples.	55
3.21	Estimation of receiver fidelity disturbance using 100 time samples of noise.	55
4.1	Map of northeast Texas and northern Louisiana (modified after Dyman and Condon (2006)).	58
4.2	Well geometry and the expected fracture orientation after Walker Jr. (1997).	58
4.3	Well logs from CGU 21-10.	60
4.4	Acquisition geometry of the Cotton Valley data set.	61
4.5	Receiver orientation obtained from Rotoscan analysis.	63
4.6	Traces of one detected event recorded in CGU 21-9.	64
4.7	Traces of one detected event recorded in CGU 22-9.	65
4.8	Component fidelity of the receivers in CGU 21-9.	66
4.9	Component fidelity of the receivers in CGU 22-9.	66
4.10	Seismograms of a detected event rotated into geographical coordinates.	67
4.11	Single receiver event detection.	68
4.12	Scheme of phase detection and identification utilizing array-specific polarization features.	69
4.13	Velocity model after Rutledge et al. (2004).	70
4.14	Resulting source images.	71
4.15	Comparison of event locations obtained by different location methods.	71
4.16	Comparison of imaging results for one time interval around the direct P-wave arrival and for two time intervals that did not fulfill the assumptions of the method.	73
5.1	Californian relief map.	76

List of Figures

5.2	Interpreted Main Hole logs from Boness and Zoback (2006) (550 m - 3000 m measured depth) and Zoback et al. (2007) (3000 m - 4000 m measured depth).	78
5.3	SAFOD receiver geometry and its pitfall for the presented location procedure.	80
5.4	Geometry of the receivers deployed in the Main Hole.	83
5.5	Waveforms of the target event of May 5, 2005.	84
5.6	Detection of P- and S-waves.	84
5.7	Rectilinearity analysis of the waveforms around the target event.	85
5.8	Polarization analysis of the waveforms around the target event.	87
5.9	Polarization analysis of the P-and S-wave of the target event.	89
5.10	Vertical slice of the P-wave velocity model (left) and the Vp-Vs-ratio model (right) through the hypocentral region of target-events.	90
5.11	Estimation of apparent velocities and effective Vp-Vs ratio from P- and S-wave arrival time data of the target event from May 5.	91
5.12	Resulting source image of the target event.	92
5.13	3D P-wave velocity models provided for the SAFOD site.	93
5.14	Locations of the target event from May 5 2005 obtained using different velocity models.	95
5.15	Seismograms of a non-target event.	97
5.16	Comparison of the moveout observed in the data and of a simulated reflection at the San Andreas Fault.	98
5.17	Hypocenters of all located events.	99
5.18	Waveform correlation of the located events.	100
5.19	Three-component waveforms of the triplet May 8 recorded at receiver no. 78.	100
C.1	Electric noise contaminating the records from 11.55 s.	131
C.2	Electric noise.	131
C.3	Cross-correlation of the noise traces between 12-14 s.	132

C.4 Grid layout of the Thurber 2006 velocity model. 136

C.5 Grid layout of the Thurber 2007 velocity model. 136

C.6 Grid layout of the Roecker 2007 velocity models. 137

List of Figures
